

according to UK REACH Regulation

### Autoprofi Diesel Anti Smoke

Revision date: 22.10.2021

Product code: 1646

Page 1 of 10

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Autoprofi Diesel Anti Smoke

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Anti Smoke Additive

### 1.3. Details of the supplier of the safety data sheet

Company name:	CTP GmbH	
Street:	Saalfelder Strasse 35h	
Place:	D-07338 Leutenberg	
Telephone:	+49 (0)36734 230-0	Telefax: +49 (0)36734 230-22
e-mail:	msds@bluechemgroup.com	
Contact person:	Jens Moeller, Dipl.-Chem.	Telephone: +49 (0)36734 230-19
Internet:	www.bluechemgroup.com	

### 1.4. Emergency telephone number:

GBK GmbH: +49-(0)6132-84463 (24/7)

#### Further Information

Article Number: 43231

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### GB CLP Regulation

Hazard categories:

Acute toxicity: Acute Tox. 4

Aspiration hazard: Asp. Tox. 1

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Harmful if swallowed.

May be fatal if swallowed and enters airways.

Toxic to aquatic life with long lasting effects.

### 2.2. Label elements

#### GB CLP Regulation

##### Hazard components for labelling

Hydrocarbons, C10-C13, n-Alkanes, Isoalkanes, Cyclics, < 2% Aromatics

2-Ethyl hexyl nitrate

Signal word: Danger

Pictograms:



#### Hazard statements

H302

Harmful if swallowed.

H304

May be fatal if swallowed and enters airways.

H411

Toxic to aquatic life with long lasting effects.

#### Precautionary statements

P101

If medical advice is needed, have product container or label at hand.

P102

Keep out of reach of children.

P260

Do not breathe vapour/aerosole.

according to UK REACH Regulation

### Autoprofi Diesel Anti Smoke

Revision date: 22.10.2021

Product code: 1646

Page 2 of 10

P270	Do not eat, drink or smoke when using this product.
P273	Avoid release to the environment.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P405	Store locked up.
P501	Dispose of this material and its container to hazardous or special waste collection point.

#### Special labelling of certain mixtures

EUH044	Risk of explosion if heated under confinement.
EUH066	Repeated exposure may cause skin dryness or cracking.

#### Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



#### Hazard statements

H302-H304

#### Precautionary statements

P101-P102-P270-P331-P405-P501

#### 2.3. Other hazards

No information available.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Chemical characterization

Synthetic agent combinations  
Lubricants  
Multifunction Diesel Fuel Additive

##### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
	Hydrocarbons, C10-C13, n-Alkanes, Isoalkanes, Cyclics, < 2% Aromatics			70 - < 75 %
	918-481-9		01-2119457273-39	
	Asp. Tox. 1; H304 EUH066			
27247-96-7	2-Ethyl hexyl nitrate			25 - < 30 %
	248-363-6		01-2119539586-27	
	Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, Aquatic Chronic 2; H332 H312 H302 H411 EUH044 EUH066			
68439-80-5	polyolefin amide alkylen amine			1 - < 5 %
	Aquatic Chronic 4; H413			

Full text of H and EUH statements: see section 16.

according to UK REACH Regulation

### Autoprofi Diesel Anti Smoke

Revision date: 22.10.2021

Product code: 1646

Page 3 of 10

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
	918-481-9	Hydrocarbons, C10-C13, n-Alkanes, Isoalkanes, Cyclics, < 2% Aromatics	70 - < 75 %
		inhalation: LC50 = >5 ppm (gases); dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	
27247-96-7	248-363-6	2-Ethyl hexyl nitrate	25 - < 30 %
		inhalation: LC50 = 4,6 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = >4820 mg/kg; oral: LD50 = >9640 mg/kg	

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### After inhalation

Move victim to fresh air. Put victim at rest and keep warm.

##### After contact with skin

Take off immediately all contaminated clothing, including underwear and shoes .  
Subsequently wash off with: Water and soap.

##### After contact with eyes

Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Consult physician.

##### After ingestion

Let water be drunken in little sips (dilution effect). Consult physician.

#### 4.2. Most important symptoms and effects, both acute and delayed

Frequently or prolonged contact with skin may cause dermal irritation.

Irritation of eyes: Irritant effect possible.

After ingestion: Harmful: may cause lung damage if swallowed.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Warning about danger of aspiration.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

##### Suitable extinguishing media

Extinguishing powder.

Sand.

Carbon dioxide (CO2).

alcohol resistant foam.

##### Unsuitable extinguishing media

High power water jet.

#### 5.2. Special hazards arising from the substance or mixture

Formation of decomposition products possible.

In case of fire and/or explosion do not breathe fumes.

#### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

#### Additional information

Cool endangered container in case of fire.

Beat down gas/vapours/mist with water spray.

Contaminated fire-fighting water must be collected separately.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

according to UK REACH Regulation

### Autoprofi Diesel Anti Smoke

Revision date: 22.10.2021

Product code: 1646

Page 4 of 10

Wear a self-contained breathing apparatus and chemical resistant suit.

Keep away from sources of ignition - No smoking.

#### **6.2. Environmental precautions**

Beat down gas/vapours/mist with water spray.

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

#### **6.3. Methods and material for containment and cleaning up**

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Prevent spread over a wide area (e.g. by containment or oil barriers).

#### **6.4. Reference to other sections**

No data

### **SECTION 7: Handling and storage**

#### **7.1. Precautions for safe handling**

##### **Advice on safe handling**

The substance should only be handled in closed apparatus or systems. Vapours / aerosols must be extracted by suction immediately at point of origin.

Avoid contact with skin and eyes.

##### **Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharges.

#### **7.2. Conditions for safe storage, including any incompatibilities**

##### **Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place.

#### **7.3. Specific end use(s)**

No information available.

### **SECTION 8: Exposure controls/personal protection**

#### **8.1. Control parameters**

#### **8.2. Exposure controls**

##### **Protective and hygiene measures**

Take off immediately all contaminated clothing

Do not breathe gas/fumes/vapour/spray.

Avoid contact with skin and eyes.

Keep away from food, drink and animal feeding stuffs.

When using do not eat, drink or smoke.

Wash hands before breaks and after work.

##### **Eye/face protection**

Wear tightly sealed safety glasses against possible splashes into the eyes. (EN 166)

##### **Hand protection**

Tested protective gloves are to be worn: NBR (Nitrile rubber). FKM (Fluoroelastomer (Viton)). (EN374)

##### **Skin protection**

Wear suitable solvent-proof protective clothing according to EN 465.

##### **Respiratory protection**

In case of accumulation of fumes/aerosols, provide adequate ventilation.

In case of fire: Wear self-contained breathing apparatus.

according to UK REACH Regulation

### Autoprofi Diesel Anti Smoke

Revision date: 22.10.2021

Product code: 1646

Page 5 of 10

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	yellow
Odour:	characteristic

#### Changes in the physical state

Boiling point or initial boiling point and boiling range:	200 - 210 °C
Flash point:	> 61 °C
Lower explosion limits:	> 0,6 vol. %
Upper explosion limits:	> 7,0 vol. %
Auto-ignition temperature:	> 200 °C
Density (at 20 °C):	0,810 - 0,825 g/cm <sup>3</sup>
Water solubility: (at 20 °C)	insoluble

#### Solubility in other solvents

Organic solvents

### 9.2. Other information

No data

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No information available.

### 10.2. Chemical stability

No decomposition when used as intended.

### 10.3. Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4. Conditions to avoid

Only use the material in places where open light, fire and other flammable sources can be kept away.

### 10.5. Incompatible materials

Oxidizing agents.  
acid, concentrated.  
Alkalis (alkalis), concentrated.

### 10.6. Hazardous decomposition products

No hazardous decomposition products are known.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity

Harmful if swallowed.

#### ATEmix calculated

ATE (oral) 1923,1 mg/kg

according to UK REACH Regulation

### Autoprofi Diesel Anti Smoke

Revision date: 22.10.2021

Product code: 1646

Page 6 of 10

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	Hydrocarbons, C10-C13, n-Alkanes, Isoalkanes, Cyclics, < 2% Aromatics				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 5000 mg/kg	Rabbit		
	inhalation (4 h) gas	LC50 >5 ppm	Rat		
27247-96-7	2-Ethyl hexyl nitrate				
	oral	LD50 >9640 mg/kg	Rat		
	dermal	LD50 >4820 mg/kg	Rabbit		
	inhalation (1 h) vapour	LC50 4,6 mg/l	Rat		
	inhalation aerosol	ATE 1,5 mg/l			

#### Irritation and corrosivity

Based on available data, the classification criteria are not met.

#### Sensitising effects

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

#### Aspiration hazard

May be fatal if swallowed and enters airways.

#### Practical experience

#### Other observations

No information available.

## SECTION 12: Ecological information

### 12.1. Toxicity

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
	Hydrocarbons, C10-C13, n-Alkanes, Isoalkanes, Cyclics, < 2% Aromatics					
	Acute fish toxicity	LC50 1000 mg/l	96 h	Oncorhynchus mykiss		
	Acute algae toxicity	ErC50 1000 mg/l	72 h	Pseudokirchneriella subcapitata		
	Acute crustacea toxicity	EC50 1000 mg/l	48 h	Daphnia magna (Big water flea)		
27247-96-7	2-Ethyl hexyl nitrate					
	Acute fish toxicity	LC50 2 mg/l	96 h	Fish		
	Acute algae toxicity	ErC50 1-10 mg/l	72 h	Algae		
	Acute crustacea toxicity	EC50 >10 mg/l	48 h	Daphnia magna		

according to UK REACH Regulation

### Autoprofi Diesel Anti Smoke

Revision date: 22.10.2021

Product code: 1646

Page 7 of 10

#### **12.2. Persistence and degradability**

No information available.

#### **12.3. Bioaccumulative potential**

Swims on the water.

Low potential of bio-accumulation.

#### **12.4. Mobility in soil**

No information available.

#### **12.5. Results of PBT and vPvB assessment**

No information available.

#### **12.6. Other adverse effects**

No information available.

#### **Further information**

Do not allow to enter into surface water or drains.

### SECTION 13: Disposal considerations

#### **13.1. Waste treatment methods**

##### **Disposal recommendations**

Do not dispose with household waste.

Do not allow to enter into surface water or drains.

Arrange about the exact waste code with the local waste disposal expert.

Have to add a Special treatment in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

##### **Contaminated packaging**

Container must be completely emptied.

Do not pierce, cut up or weld unclean container. (Explosion hazard.)

### SECTION 14: Transport information

#### **Land transport (ADR/RID)**

##### **14.1. UN number:**

UN 3082

##### **14.2. UN proper shipping name:**

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Solvent naphtha (petroleum, gasoline), heavy arom.

2-Ethyl hexyl nitrate

##### **14.3. Transport hazard class(es):**

9

##### **14.4. Packing group:**

III

Hazard label:

9



Classification code:

M6

Special Provisions:

274 335 375 601

Limited quantity:

5 L

Excepted quantity:

E1

Transport category:

3

Hazard No:

90

Tunnel restriction code:

-

#### **Inland waterways transport (ADN)**

##### **14.1. UN number:**

UN 3082

according to UK REACH Regulation

### Autoprofi Diesel Anti Smoke

Revision date: 22.10.2021

Product code: 1646

Page 8 of 10

#### 14.2. UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
Solvent naphtha (petroleum, gasoline), heavy arom.  
2-Ethyl hexyl nitrate

#### 14.3. Transport hazard class(es):

9

#### 14.4. Packing group:

III

Hazard label:

9



Classification code:

M6

Special Provisions:

274 335 375 601

Limited quantity:

5 L

Excepted quantity:

E1

#### Marine transport (IMDG)

#### 14.1. UN number:

UN 3082

#### 14.2. UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
Solvent naphtha (petroleum, gasoline), heavy arom.  
2-Ethyl hexyl nitrate

#### 14.3. Transport hazard class(es):

9

#### 14.4. Packing group:

III

Hazard label:

9



Marine pollutant:

P

Special Provisions:

274, 335, 969

Limited quantity:

5 L

Excepted quantity:

E1

EmS:

F-A, S-F

#### Air transport (ICAO-TI/IATA-DGR)

#### 14.1. UN number:

UN 3082

#### 14.2. UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
Solvent naphtha (petroleum, gasoline), heavy arom.  
2-Ethyl hexyl nitrate

#### 14.3. Transport hazard class(es):


9

#### 14.4. Packing group:

III

Hazard label:

9



Special Provisions:

A97 A158 A197 A215

Limited quantity Passenger:

30 kg G

Passenger LQ:

Y964

Excepted quantity:

E1

IATA-packing instructions - Passenger:

964

IATA-max. quantity - Passenger:

450 L

IATA-packing instructions - Cargo:

964

IATA-max. quantity - Cargo:

450 L

#### 14.5. Environmental hazards



according to UK REACH Regulation

### Autoprofi Diesel Anti Smoke

Revision date: 22.10.2021

Product code: 1646

Page 9 of 10

ENVIRONMENTALLY HAZARDOUS: Yes



Danger releasing substance: Solvent naphtha (petroleum, gasoline), heavy arom.  
2-Ethyl hexyl nitrate

#### 14.6. Special precautions for user

No information available.

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No information available.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28

##### Additional information

Contains:

> 30 % hydrocarbons, aliphatic.

< 5 % hydrocarbons, aromatic.

##### National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

#### 15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

Hydrocarbons, C10-C13, n-Alkanes, Isoalkanes, Cyclics, < 2% Aromatics

2-Ethyl hexyl nitrate

### SECTION 16: Other information

#### Changes

This data sheet contains changes from the previous version in section(s): 2,3,9,11,12,14,15.

#### Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Acute Tox. 4; H302	Calculation method
Asp. Tox. 1; H304	Calculation method
Aquatic Chronic 2; H411	Calculation method

#### Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH044	Risk of explosion if heated under confinement.
EUH066	Repeated exposure may cause skin dryness or cracking.

#### Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

according to UK REACH Regulation

### Autoprofi Diesel Anti Smoke

Revision date: 22.10.2021

Product code: 1646

Page 10 of 10

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*