

LPG System Clean & Protect

Revision date: 28.10.2021

Product code: 2095

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

LPG System Clean & Protect

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Cleaning agent for Fuel Systems

1.3. Details of the supplier of the safety data sheet

Company name:	CTP GmbH	
Street:	Saalfelder Strasse 35h	
Place:	D-07338 Leutenberg	
Telephone:	+49 (0)36734 230-0	Telefax: +49 (0)36734 230-22
e-mail:	msds@bluechemgroup.com	
Contact person:	Jens Moeller, Dipl.-Chem.	Telephone: +49 (0)36734 230-19
Internet:	www.bluechemgroup.com	

1.4. Emergency telephone number: GBK GmbH: +49-(0)6132-84463 (24/7)**Further Information**

Article Number: 33356

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****GB CLP Regulation**

Hazard categories:
Aerosol: Aerosol 1
Aspiration hazard: Asp. Tox. 1
Skin corrosion/irritation: Skin Irrit. 2
Serious eye damage/eye irritation: Eye Irrit. 2
Specific target organ toxicity - single exposure: STOT SE 3
Hazardous to the aquatic environment: Aquatic Chronic 3
Hazard Statements:
Extremely flammable aerosol.
Pressurised container: May burst if heated.
May be fatal if swallowed and enters airways.
Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness.
Harmful to aquatic life with long lasting effects.

2.2. Label elements**GB CLP Regulation****Hazard components for labelling**

Low boiling point hydrogen treated naphtha, Naphtha (petroleum, gasoline), hydrotreated light ethyl acetate

Signal word: Danger**Pictograms:**

LPG System Clean & Protect

Revision date: 28.10.2021

Product code: 2095

Page 2 of 10

Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing aerosole.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves and eye/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P312	Call a POISON CENTER/doctor if you feel unwell.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405	Store locked up.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of this material and its container to hazardous or special waste collection point.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



Hazard statements

H222-H229-H336-H412

Precautionary statements

P101-P102-P210-P211-P251-P271-P312-P405-P410+P412

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Alcohols.
ketone.
Corrosion inhibitors.
Additives
Organic solvents

LPG System Clean & Protect

Revision date: 28.10.2021

Product code: 2095

Page 3 of 10

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
68476-85-7	Petroleum gas, Petroleum gases, liquefied			75 - < 80 %
	270-704-2			
	Flam. Gas 1A, Compressed gas; H220 H280			
64742-49-0	Low boiling point hydrogen treated naphtha, Naphtha (petroleum, gasoline), hydrotreated light			5 - < 15 %
	927-510-4		01-2119475515-33	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
124-38-9	carbon dioxide			5 - < 10 %
	204-696-9			
	Compressed gas; H280			
141-78-6	ethyl acetate			1 - < 5 %
	205-500-4		01-2119475103-46	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
141-78-6	205-500-4	ethyl acetate	1 - < 5 %
	inhalation: LC50 = 58 mg/l (vapours); dermal: LD50 = 18000 mg/kg; oral: LD50 = 5600 mg/kg		

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove affected person from the danger area and lay down.
Change contaminated clothing.

After inhalation

Provide fresh air. If victim is at risk of losing consciousness, position and transport on their side.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap.
In case of skin irritation, seek medical treatment.

After contact with eyes

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Consult physician.

4.2. Most important symptoms and effects, both acute and delayed

Frequently or prolonged contact with skin may cause dermal irritation.
Irritation of eyes: Irritant effect possible.
Harmful: danger of serious damage to health by prolonged exposure through inhalation.

4.3. Indication of any immediate medical attention and special treatment needed

The following symptoms may occur:
unconsciousness. Intoxication. vomiting. drowsiness. Headache.



LPG System Clean & Protect

Revision date: 28.10.2021

Product code: 2095

Page 4 of 10

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguishing powder.
Carbon dioxide (CO₂).
Water fog.
alcohol resistant foam.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Swims on the water. Vapours are heavier than air and will spread at floor level.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Cool endangered container in case of fire.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. Wear suitable solvent-proof protective clothing according to EN 465. Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes.
Do not breathe gas/fumes/vapour/spray.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

6.4. Reference to other sections

Explosive. Vapours may form explosive mixtures with air.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep only in the original container in a cool, well-ventilated place.
If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Advice on protection against fire and explosion

Vapours may form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

The floor should be leak tight, jointless and not absorbent. Keep only in the original container in a cool, well-ventilated place. Do not store at temperatures over: 50 °C
Heating causes rise in pressure with risk of bursting.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

LPG System Clean & Protect

Revision date: 28.10.2021

Product code: 2095

Page 5 of 10

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
124-38-9	Carbon dioxide	5000	9150		TWA (8 h)	WEL
		15000	27400		STEL (15 min)	WEL
141-78-6	Ethyl acetate	200	734		TWA (8 h)	WEL
		400	1468		STEL (15 min)	WEL
68476-85-7	Liquefied petroleum gas	1000	1750		TWA (8 h)	WEL
		1250	2180		STEL (15 min)	WEL

8.2. Exposure controls

Protective and hygiene measures

Keep away from food, drink and animal feedingstuffs.

Remove contaminated, saturated clothing immediately. Wash hands before breaks and after work.

Do not breathe gas/fumes/vapour/spray. Avoid contact with skin and eyes.

Eye/face protection

Wear tightly sealed safety glasses against possible splashes into the eyes.

Hand protection

Tested protective gloves are to be worn: FKM (Fluoroelastomer (Viton)).NBR (Nitrile rubber).

Respiratory protection

Have to care for a good Ventilation at workplace.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Aerosol
Colour:	colourless
Odour:	characteristic

Changes in the physical state

Boiling point or initial boiling point and boiling range: <=35 °C

Flash point: < 0 °C

Auto-ignition temperature: 400 °C

Density (at 20 °C): 0,623 g/cm³

Water solubility: (at 20 °C) insoluble

9.2. Other information

No data

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No decomposition when used as intended.

10.3. Possibility of hazardous reactions

No dangerous reactions are known.

LPG System Clean & Protect

Revision date: 28.10.2021

Product code: 2095

Page 6 of 10

10.4. Conditions to avoid

Do not store at temperatures over: 50 °C
Keep away from heat.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No dangerous reactions are known.
No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
141-78-6	ethyl acetate				
	oral	LD50 mg/kg	5600	Rat	
	dermal	LD50 mg/kg	18000	Rabbit	
	inhalation (4 h) vapour	LC50	58 mg/l	Rat	

Irritation and corrosivity

Causes skin irritation.
Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Low boiling point hydrogen treated naphtha, Naphtha (petroleum, gasoline), hydrotreated light)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

Practical experience

Other observations

No information available.

SECTION 12: Ecological information

12.1. Toxicity

LPG System Clean & Protect

Revision date: 28.10.2021

Product code: 2095

Page 7 of 10

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64742-49-0	Low boiling point hydrogen treated naphtha, Naphtha (petroleum, gasoline), hydrotreated light					
	Acute crustacea toxicity	EC50 mg/l	1-10	48 h	Daphnia magna	
	Crustacea toxicity	NOEC	1 mg/l		Daphnia magna	

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

Swims on the water.

Low potential of bio-accumulation.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

No information available.

12.6. Other adverse effects

No information available.

Further information

Do not empty into drains or the aquatic environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

According to EAKV, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Arrange about the exact waste code with the local waste disposal expert.

Do not dispose with household waste.

List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

Contaminated packaging

Dispose of waste according to applicable legislation. Contaminated packing must be completely emptied and can be re-used following appropriate cleaning.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:

UN 1950

14.2. UN proper shipping name:

AEROSOLS

Petroleum gas, Petroleum gases, liquefied

14.3. Transport hazard class(es):

2

14.4. Packing group:

-

Hazard label:

2.1



LPG System Clean & Protect

Revision date: 28.10.2021

Product code: 2095

Page 8 of 10

Classification code: 5F
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L
 Excepted quantity: E0
 Transport category: 2
 Hazard No: -
 Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
 Petroleum gas, Petroleum gases, liquefied
14.3. Transport hazard class(es): 2
14.4. Packing group: -
 Hazard label: 2.1



Classification code: 5F
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L
 Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
 Petroleum gas, Petroleum gases, liquefied
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
 Hazard label: 2.1



Marine pollutant: -
 Special Provisions: 63, 190, 277, 327, 344, 381, 959
 Limited quantity: 1000 mL
 Excepted quantity: E0
 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS, FLAMMABLE
 Petroleum gas, Petroleum gases, liquefied
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
 Hazard label: 2.1



Special Provisions: A145 A167 A802
 Limited quantity Passenger: 30 kg G
 Passenger LQ: Y203



Safety Data Sheet

according to UK REACH Regulation

LPG System Clean & Protect

Revision date: 28.10.2021

Product code: 2095

Page 9 of 10

Excepted quantity: E0
IATA-packing instructions - Passenger: 203
IATA-max. quantity - Passenger: 75 kg
IATA-packing instructions - Cargo: 203
IATA-max. quantity - Cargo: 150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No information available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28

Additional information

Contains:

> 30 % aliphatic hydrocarbons

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

Low boiling point hydrogen treated naphtha, Naphtha (petroleum, gasoline), hydrotreated light ethyl acetate

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,8,11,12,14,15.

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Bridging principle "Aerosols"
Eye Irrit. 2; H319	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H220 Extremely flammable gas.
H222 Extremely flammable aerosol.
H225 Highly flammable liquid and vapour.
H229 Pressurised container: May burst if heated.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.



Safety Data Sheet

bluechem 
GROUP

according to UK REACH Regulation

LPG System Clean & Protect

Revision date: 28.10.2021

Product code: 2095

Page 10 of 10

H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)