AUTOPROFI

Common-Rail Diesel System Clean & Protect

Product properties

Common Rail Diesel System Clean & Protect has been specifically developed for all high pressure direct injection diesel engines with Common Rail or pump injector. This high technology product, developed from extensive research, is designed to meet the exact requirementRemoves smallest dirt from the entire diesel system, destroys and absorbs water bubbles in the fuel. Exceeds HFRRTest according to DIN EN ISO 12156-1.

Area of application

For all diesel engines, particularly recommended for direct fuel injection and common-rail systems.

Application

Add to the fuel tank.

Consumption 250 ml for 60 ltr. diesel

Reaction time Works during operation.

Technical data

Physical state: liquid Colour: brown Odour: aromatic Initial boiling point and boiling range: 200 - 210 °C Flashpoint: 45 °C Lower explosion limit: > 0,6 Vol.-% Upper explosion limit: > 7,0 Vol.-% Ignition temperature: > 200 °C Vapour pressure (at 68 °F): > 8 hPa Density at 68 °F: 0.824 - 0.9 g/cm³ Water resistant

Available sizes	ltem no.	PU
250ml	43221	24



Our information is based on careful examination and may be considered as reliable. However, all information supplied is non-binding advise. No liability for any printing errors. Technical modifications and errors are exempted.

