

**Valves & Injection Cleaner**

Revision date: 17.05.2022

Product code: 1541

Page 1 of 13

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

Valves & Injection Cleaner

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Use of the substance/mixture**

Cleaning agent for Fuel Systems

**1.3. Details of the supplier of the safety data sheet**

Company name:	CTP GmbH	
Street:	Saalfelder Strasse 35h	
Place:	D-07338 Leutenberg	
Telephone:	+49 (0)36734 230-0	Telefax: +49 (0)36734 230-22
e-mail:	msds@bluechemgroup.com	
Contact person:	Jens Moeller, Dipl.-Chem.	Telephone: +49 (0)36734 230-19
Internet:	www.bluechemgroup.com	

**1.4. Emergency telephone number:** GBK GmbH: +49-(0)6132-84463 (24/7)

**Further Information**

Article Number: 2231, 2232, 2233, 2235, 2237, 2238, 2239

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**GB CLP Regulation**

Flam. Liq. 2; H225  
Acute Tox. 4; H332  
Asp. Tox. 1; H304  
Skin Irrit. 2; H315  
Eye Irrit. 2; H319  
STOT SE 3; H335  
STOT SE 3; H336  
STOT RE 2; H373  
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

**2.2. Label elements**

**GB CLP Regulation**

**Hazard components for labelling**

xylene  
propan-2-ol; isopropyl alcohol; isopropanol  
acetone; propan-2-one; propanone  
Hydrocarbons, C9-C11, n-Alkanes, Isoalkanes, Cyclenes, < 2% Aromates

**Signal word:** Danger

**Pictograms:**



**Hazard statements**

H225 Highly flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.

**Valves & Injection Cleaner**

Revision date: 17.05.2022

Product code: 1541

Page 2 of 13

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P405	Store locked up.
P501	Dispose of this material and its container to hazardous or special waste collection point.

**Labelling of packages where the contents do not exceed 125 ml**

**Signal word:** Danger

**Pictograms:**



**Hazard statements**

H304-H332-H335-H336-H373-H412

**Precautionary statements**

P101-P102-P260-P271-P301+P310-P331-P405-P501

**2.3. Other hazards**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**

**Chemical characterization**

Detergents, Dispersants  
Synthetic agent combinations  
Solvent mixture

**Valves & Injection Cleaner**

Revision date: 17.05.2022

Product code: 1541

Page 3 of 13

**Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
1330-20-7	xylene			30 - < 35 %
	215-535-7		01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H226 H332 H312 H319 H335 H373 H304 H412			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			20 - < 25 %
	200-661-7		01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
67-64-1	acetone; propan-2-one; propanone			20 - < 25 %
	200-662-2		01-2119471330-49	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
64742-48-9	Hydrocarbons, C9-C11, n-Alkanes, Isoalkanes, Cyclenes, < 2% Aromates			15 - < 20 %
	919-857-5		01-2119463258-33	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1; H226 H336 H304 EUH066			
64742-47-8	Hydrocarbons, C9-C11, Isoalkanes, Cycloalkanes, < 2% Aromates			5 - < 10 %
	920-134-1		01-2119480153-44	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H336 H304 H411 EUH066			
	Poly[oxy(1,2-butanediyl)], .alpha.-(3-aminopropyl)-.gamma.-hydroxy-, C11-14-isoalkyl ethers, C13-rich (Polyetheramines)			1 - < 5 %
	Aquatic Chronic 2; H411			

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
1330-20-7	215-535-7	xylene	30 - < 35 %
		inhalation: LC50 = 21,7 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 3200 mg/kg; oral: LD50 = 4300 mg/kg	
67-63-0	200-661-7	propan-2-ol; isopropyl alcohol; isopropanol	20 - < 25 %
		inhalation: LC50 = 47,5 mg/l (vapours); dermal: LD50 = 12800 mg/kg; oral: LD50 = 5280 mg/kg	
67-64-1	200-662-2	acetone; propan-2-one; propanone	20 - < 25 %
		inhalation: LC50 = 76 mg/l (vapours); dermal: LD50 = 20000 mg/kg; oral: LD50 = 5800 mg/kg	
64742-48-9	919-857-5	Hydrocarbons, C9-C11, n-Alkanes, Isoalkanes, Cyclenes, < 2% Aromates	15 - < 20 %
		inhalation: LC50 = >5 mg/l (dusts or mists); dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg	
64742-47-8	920-134-1	Hydrocarbons, C9-C11, Isoalkanes, Cycloalkanes, < 2% Aromates	5 - < 10 %
		inhalation: LC50 = >5 mg/l (dusts or mists); dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg	
		Poly[oxy(1,2-butanediyl)], .alpha.-(3-aminopropyl)-.gamma.-hydroxy-, C11-14-isoalkyl ethers, C13-rich (Polyetheramines)	1 - < 5 %
		dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg	

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**Valves & Injection Cleaner**

Revision date: 17.05.2022

Product code: 1541

Page 4 of 13

**General information**

Move victim to fresh air. Put victim at rest and keep warm.

**After inhalation**

Move victim to fresh air. Put victim at rest and keep warm.

In case of difficulties of breathing consult physician.

If victim is at risk of losing consciousness, position and transport on their side.

**After contact with skin**

Take off immediately all contaminated clothing, including underwear and shoes .

After contact with skin, wash immediately with plenty of water and soap.

Rub greasy ointment into the skin.

**After contact with eyes**

Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart.

Consult physician.

**After ingestion**

Let water be drunken in little sips (dilution effect). Consult physician.

**4.2. Most important symptoms and effects, both acute and delayed**

Frequently or prolonged contact with skin may cause dermal irritation.

Irritation of eyes: Irritant effect possible.

After ingestion: Harmful: may cause lung damage if swallowed.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

**4.3. Indication of any immediate medical attention and special treatment needed**

Warning about danger of aspiration.

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media**

Extinguishing powder.

Sand.

alcohol resistant foam.

Carbon dioxide (CO<sub>2</sub>).

**Unsuitable extinguishing media**

High power water jet.

**5.2. Special hazards arising from the substance or mixture**

Formation of decomposition products possible.

In case of fire and/or explosion do not breathe fumes.

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

**Additional information**

Cool endangered container in case of fire.

Contaminated fire-fighting water must be collected separately.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

In case of fire: Wear self-contained breathing apparatus.

Keep away from sources of ignition - No smoking.

**6.2. Environmental precautions**

Beat down gas/vapours/mist with water spray.

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

## Valves & Injection Cleaner

Revision date: 17.05.2022

Product code: 1541

Page 5 of 13

### 6.3. Methods and material for containment and cleaning up

Prevent spread over a wide area (e.g. by containment or oil barriers).  
Wipe up with absorbent material (eg. cloth, fleece).

### 6.4. Reference to other sections

No data

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Closed devices. Vapours / aerosols must be extracted by suction immediately at point of origin.  
Avoid contact with skin and eyes.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

#### Further information on storage conditions

Packaging materials: metal.

### 7.3. Specific end use(s)

No information available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

#### Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol	urine	Post shift

### 8.2. Exposure controls

#### Protective and hygiene measures

Do not eat, drink, smoke or sneeze at the workplace. Wash hands before breaks and after work.

#### Eye/face protection

Wear tightly sealed safety glasses against possible splashes into the eyes. (DIN EN 166)

#### Hand protection

Tested protective gloves are to be worn: Butyl rubber. (EN ISO 374)

**Valves & Injection Cleaner**

Revision date: 17.05.2022

Product code: 1541

Page 6 of 13

**Skin protection**

Wear suitable solvent-proof protective clothing according to EN 465.

**Respiratory protection**

Provide for good ventilation, when develop aerosols/mist. In case of insufficient ventilation, wear suitable respiratory equipment.

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	blue
Odour:	aromatic

**Changes in the physical state**

Boiling point or initial boiling point and boiling range: 110 - 116 °C

Flash point: -5 °C

Lower explosion limits: 0,6 vol. %

Upper explosion limits: 12 vol. %

Auto-ignition temperature: > 200 °C

Vapour pressure: 20 hPa  
(at 20 °C)

Density (at 20 °C): 0,807 g/cm<sup>3</sup>

Water solubility: insoluble  
(at 20 °C)

**Solubility in other solvents**

Organic solvents

**9.2. Other information**

No data

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

No information available.

**10.2. Chemical stability**

No information available.

**10.3. Possibility of hazardous reactions**

No information available.

**10.4. Conditions to avoid**

Only use the material in places where open light, fire and other flammable sources can be kept away.

**10.5. Incompatible materials**

Oxidizing agents. acid, concentrated. Alkalis (alkalis), concentrated.

**10.6. Hazardous decomposition products**

Carbon monoxide (CO).  
Carbon dioxide (CO<sub>2</sub>).

**SECTION 11: Toxicological information**

**11.1. Information on toxicological effects**

**Valves & Injection Cleaner**

Revision date: 17.05.2022

Product code: 1541

Page 7 of 13

**Acute toxicity**

Harmful if inhaled.

**ATEmix calculated**

ATE (inhalation dust/mist) 4,839 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
1330-20-7	xylene				
	oral	LD50 mg/kg 4300	Rat		
	dermal	LD50 mg/kg 3200	Rabbit		
	inhalation (4 h) vapour	LC50 21,7 mg/l	Rat		
	inhalation dust/mist	ATE 1,5 mg/l			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol				
	oral	LD50 mg/kg 5280	Rat		
	dermal	LD50 mg/kg 12800	Rabbit		
	inhalation (4 h) vapour	LC50 47,5 mg/l	Rat		
67-64-1	acetone; propan-2-one; propanone				
	oral	LD50 mg/kg 5800	Rat	RTECS	
	dermal	LD50 mg/kg 20000	Rabbit	IUCLID	
	inhalation (4 h) vapour	LC50 76 mg/l	Rat		
64742-48-9	Hydrocarbons, C9-C11, n-Alkanes, Isoalkanes, Cyclenes, < 2% Aromates				
	oral	LD50 mg/kg >5000	Rat		
	dermal	LD50 mg/kg >5000	Rabbit		
	inhalation (4 h) dust/mist	LC50 >5 mg/l	Rat		
64742-47-8	Hydrocarbons, C9-C11, Isoalkanes, Cycloalkanes, < 2% Aromates				
	oral	LD50 mg/kg >5000	Rat		
	dermal	LD50 mg/kg >5000	Rabbit		
	inhalation (4 h) dust/mist	LC50 >5 mg/l	Rat		
	Poly[oxy(1,2-butanediyl)], .alpha.-(3-aminopropyl)-.gamma.-hydroxy-, C11-14-isoalkyl ethers, C13-rich (Polyetheramines)				
	oral	LD50 mg/kg >5000	Rat		
	dermal	LD50 mg/kg >2000	Rabbit		

**Irritation and corrosivity**

Causes skin irritation.

Causes serious eye irritation.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Valves & Injection Cleaner**

Revision date: 17.05.2022

Product code: 1541

Page 8 of 13

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause respiratory irritation. (xylene)

May cause drowsiness or dizziness. (propan-2-ol; isopropyl alcohol; isopropanol; acetone; propan-2-one; propanone)

**STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure. (xylene)

**Aspiration hazard**

May be fatal if swallowed and enters airways.

**Practical experience**

**Other observations**

No information available.

**SECTION 12: Ecological information**

**12.1. Toxicity**



**Valves & Injection Cleaner**

Revision date: 17.05.2022

Product code: 1541

Page 9 of 13

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
1330-20-7	xylene					
	Acute fish toxicity	LC50 mg/l	26,7	96 h	Pimephales promelas	
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
	Acute fish toxicity	LC50 mg/l	9640	96 h	Pimephales promelas	
	Acute algae toxicity	ErC50 mg/l	1000	72 h	Algae	
	Acute crustacea toxicity	EC50 mg/l	13299	48 h	Daphnia magna	
67-64-1	acetone; propan-2-one; propanone					
	Acute fish toxicity	LC50 mg/l	5540	96 h	Onchorhynchus mykiss	
	Acute crustacea toxicity	EC50 mg/l	6100	48 h	Daphnia magna	
64742-48-9	Hydrocarbons, C9-C11, n-Alkanes, Isoalkanes, Cyclenes, < 2% Aromates					
	Acute fish toxicity	LC50 mg/l	>1000	96 h	Oncorhynchus mykiss	
	Acute algae toxicity	ErC50 mg/l	>1000	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50 mg/l	1000	48 h	Daphnia magna	
64742-47-8	Hydrocarbons, C9-C11, Isoalkanes, Cycloalkanes, < 2% Aromates					
	Acute fish toxicity	LC50 mg/l	>1000	96 h	Oncorhynchus mykiss	
	Acute algae toxicity	ErC50 mg/l	>1000	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50 mg/l	1000	48 h	Daphnia magna	
	Poly[oxy(1,2-butanediyl)], .alpha.-(3-aminopropyl)-.gamma.-hydroxy-, C11-14-isoalkyl ethers, C13-rich (Polyetheramines)					
	Acute fish toxicity	LC50 mg/l	1-10	96 h	Fish	
	Acute algae toxicity	ErC50 mg/l	10-100	72 h	Algae	

**12.2. Persistence and degradability**

No information available.

**12.3. Bioaccumulative potential**

Swims on the water. Low potential of bio-accumulation.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
67-64-1	acetone; propan-2-one; propanone	-0,24

**12.4. Mobility in soil**

No information available.

**12.6. Other adverse effects**

No information available.

**Valves & Injection Cleaner**

Revision date: 17.05.2022

Product code: 1541

Page 10 of 13

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Disposal recommendations**

Do not dispose with household waste.

Do not allow to enter into surface water or drains.

Have to add a Special treatment in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

Arrange about the exact waste code with the local waste disposal expert.

**Contaminated packaging**

Contaminated packing must be completely emptied and can be re-used following appropriate cleaning.

Do not pierce, cut up or weld unclean container. (Explosion hazard.)

**SECTION 14: Transport information**

**Land transport (ADR/RID)**

**14.1. UN number:**

UN 1993

**14.2. UN proper shipping name:**

FLAMMABLE LIQUID, N.O.S.

(xylene, propan-2-ol; isopropyl alcohol; isopropanol  
acetone; propan-2-one; propanone, Hydrocarbons, C9-C11, n-Alkanes,  
Isoalkanes, Cyclenes, < 2% Aromates)

**14.3. Transport hazard class(es):**

3

**14.4. Packing group:**

II

Hazard label:

3



Classification code:

F1

Special Provisions:

274 601 640D

Limited quantity:

1 L

Excepted quantity:

E2

Transport category:

2

Hazard No:

33

Tunnel restriction code:

D/E

**Inland waterways transport (ADN)**

**14.1. UN number:**

UN 1993

**14.2. UN proper shipping name:**

FLAMMABLE LIQUID, N.O.S.

(xylene, propan-2-ol; isopropyl alcohol; isopropanol  
acetone; propan-2-one; propanone, Hydrocarbons, C9-C11, n-Alkanes,  
Isoalkanes, Cyclenes, < 2% Aromates)

**14.3. Transport hazard class(es):**

3

**14.4. Packing group:**

II

Hazard label:

3



Classification code:

F1

Special Provisions:

274 601 640D

Limited quantity:

1 L

Excepted quantity:

E2


**Valves & Injection Cleaner**

Revision date: 17.05.2022


Product code: 1541

Page 11 of 13

**Marine transport (IMDG)**

<b>14.1. UN number:</b>	UN 1993
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, N.O.S. (xylene, propan-2-ol; isopropyl alcohol; isopropanol acetone; propan-2-one; propanone, Hydrocarbons, C9-C11, n-Alkanes, Isoalkanes, Cyclenes, < 2% Aromates)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3
	
Marine pollutant:	-
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-E, S-E

**Air transport (ICAO-TI/IATA-DGR)**

<b>14.1. UN number:</b>	UN 1993
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, N.O.S. (xylene, propan-2-ol; isopropyl alcohol; isopropanol acetone; propan-2-one; propanone, Hydrocarbons, C9-C11, n-Alkanes, Isoalkanes, Cyclenes, < 2% Aromates)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3
	
Special Provisions:	A3
Limited quantity Passenger:	1 L
Passenger LQ:	Y341
Excepted quantity:	E2
IATA-packing instructions - Passenger:	353
IATA-max. quantity - Passenger:	5 L
IATA-packing instructions - Cargo:	364
IATA-max. quantity - Cargo:	60 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

No information available.

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

No information available.

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU regulatory information**

**Valves & Injection Cleaner**

Revision date: 17.05.2022

Product code: 1541

Page 12 of 13

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 40, Entry 75

2010/75/EU (VOC): 98,25 % (792,878 g/l)

2004/42/EC (VOC): 98,25 % (792,878 g/l)

Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

**Additional information**

Contains:

> 30 % hydrocarbons, aromatic.

15 - 30 % hydrocarbons, aliphatic.

**National regulatory information**

Water hazard class (D): 2 - obviously hazardous to water

**15.2. Chemical safety assessment**

For the following substances of this mixture a chemical safety assessment has been carried out:

xylene

propan-2-ol; isopropyl alcohol; isopropanol

acetone; propan-2-one; propanone

Hydrocarbons, C9-C11, n-Alkanes, Isoalkanes, Cyclenes, < 2% Aromates

Hydrocarbons, C9-C11, Isoalkanes, Cycloalkanes, < 2% Aromates

**SECTION 16: Other information**

**Classification for mixtures and used evaluation method according to GB CLP Regulation**

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Acute Tox. 4; H332	Calculation method
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H335	Calculation method
STOT SE 3; H336	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 3; H412	Calculation method

**Relevant H and EUH statements (number and full text)**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

**Further Information**

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

**Valves & Injection Cleaner**

Revision date: 17.05.2022

Product code: 1541

Page 13 of 13

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*