

Valves & Injection Cleaner

Revision date: 17.05.2022

Product code: 1541

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Valves & Injection Cleaner

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Cleaning agent for Fuel Systems

1.3. Details of the supplier of the safety data sheet

Company name:	CTP GmbH	
Street:	Saalfelder Strasse 35h	
Place:	D-07338 Leutenberg	
Telephone:	+49 (0)36734 230-0	Telefax: +49 (0)36734 230-22
e-mail:	msds@bluechemgroup.com	
Contact person:	Jens Moeller, Dipl.-Chem.	Telephone: +49 (0)36734 230-19
Internet:	www.bluechemgroup.com	

1.4. Emergency telephone number:

GBK GmbH: +49-(0)6132-84463 (24/7)

Further Information

Article Number: 2231, 2232, 2233, 2235, 2237, 2238, 2239

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 2; H225
Acute Tox. 4; H332
Asp. Tox. 1; H304
Skin Irrit. 2; H315
Eye Irrit. 2; H319
STOT SE 3; H335
STOT SE 3; H336
STOT RE 2; H373
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

xylene
propan-2-ol; isopropyl alcohol; isopropanol
acetone; propan-2-one; propanone
Hydrocarbons, C9-C11, n-Alkanes, Isoalkanes, Cyclenes, < 2% Aromates

Signal word: Danger

Pictograms:



Hazard statements

H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.

Valves & Injection Cleaner

Revision date: 17.05.2022

Product code: 1541

Page 2 of 13

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P405	Store locked up.
P501	Dispose of this material and its container to hazardous or special waste collection point.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



Hazard statements

H304-H332-H335-H336-H373-H412

Precautionary statements

P101-P102-P260-P271-P301+P310-P331-P405-P501

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Detergents, Dispersants
Synthetic agent combinations
Solvent mixture

Valves & Injection Cleaner

Revision date: 17.05.2022

Product code: 1541

Page 3 of 13

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
1330-20-7	xylene			30 - < 35 %
	215-535-7		01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H226 H332 H312 H319 H335 H373 H304 H412			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			20 - < 25 %
	200-661-7		01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
67-64-1	acetone; propan-2-one; propanone			20 - < 25 %
	200-662-2		01-2119471330-49	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
64742-48-9	Hydrocarbons, C9-C11, n-Alkanes, Isoalkanes, Cyclenes, < 2% Aromates			15 - < 20 %
	919-857-5		01-2119463258-33	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1; H226 H336 H304 EUH066			
64742-47-8	Hydrocarbons, C9-C11, Isoalkanes, Cycloalkanes, < 2% Aromates			5 - < 10 %
	920-134-1		01-2119480153-44	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H336 H304 H411 EUH066			
	Poly[oxy(1,2-butanediyl)], .alpha.-(3-aminopropyl)-.gamma.-hydroxy-, C11-14-isoalkyl ethers, C13-rich (Polyetheramines)			1 - < 5 %
	Aquatic Chronic 2; H411			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
1330-20-7	215-535-7	xylene	30 - < 35 %
		inhalation: LC50 = 21,7 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 3200 mg/kg; oral: LD50 = 4300 mg/kg	
67-63-0	200-661-7	propan-2-ol; isopropyl alcohol; isopropanol	20 - < 25 %
		inhalation: LC50 = 47,5 mg/l (vapours); dermal: LD50 = 12800 mg/kg; oral: LD50 = 5280 mg/kg	
67-64-1	200-662-2	acetone; propan-2-one; propanone	20 - < 25 %
		inhalation: LC50 = 76 mg/l (vapours); dermal: LD50 = 20000 mg/kg; oral: LD50 = 5800 mg/kg	
64742-48-9	919-857-5	Hydrocarbons, C9-C11, n-Alkanes, Isoalkanes, Cyclenes, < 2% Aromates	15 - < 20 %
		inhalation: LC50 = >5 mg/l (dusts or mists); dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg	
64742-47-8	920-134-1	Hydrocarbons, C9-C11, Isoalkanes, Cycloalkanes, < 2% Aromates	5 - < 10 %
		inhalation: LC50 = >5 mg/l (dusts or mists); dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg	
		Poly[oxy(1,2-butanediyl)], .alpha.-(3-aminopropyl)-.gamma.-hydroxy-, C11-14-isoalkyl ethers, C13-rich (Polyetheramines)	1 - < 5 %
		dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg	

SECTION 4: First aid measures

4.1. Description of first aid measures

Valves & Injection Cleaner

Revision date: 17.05.2022

Product code: 1541

Page 4 of 13

General information

Move victim to fresh air. Put victim at rest and keep warm.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm.

In case of difficulties of breathing consult physician.

If victim is at risk of losing consciousness, position and transport on their side.

After contact with skin

Take off immediately all contaminated clothing, including underwear and shoes .

After contact with skin, wash immediately with plenty of water and soap.

Rub greasy ointment into the skin.

After contact with eyes

Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart.

Consult physician.

After ingestion

Let water be drunken in little sips (dilution effect). Consult physician.

4.2. Most important symptoms and effects, both acute and delayed

Frequently or prolonged contact with skin may cause dermal irritation.

Irritation of eyes: Irritant effect possible.

After ingestion: Harmful: may cause lung damage if swallowed.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

4.3. Indication of any immediate medical attention and special treatment needed

Warning about danger of aspiration.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguishing powder.

Sand.

alcohol resistant foam.

Carbon dioxide (CO₂).

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Formation of decomposition products possible.

In case of fire and/or explosion do not breathe fumes.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Cool endangered container in case of fire.

Contaminated fire-fighting water must be collected separately.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

In case of fire: Wear self-contained breathing apparatus.

Keep away from sources of ignition - No smoking.

6.2. Environmental precautions

Beat down gas/vapours/mist with water spray.

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Valves & Injection Cleaner

Revision date: 17.05.2022

Product code: 1541

Page 5 of 13

6.3. Methods and material for containment and cleaning up

Prevent spread over a wide area (e.g. by containment or oil barriers).
Wipe up with absorbent material (eg. cloth, fleece).

6.4. Reference to other sections

No data

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Closed devices. Vapours / aerosols must be extracted by suction immediately at point of origin.
Avoid contact with skin and eyes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Further information on storage conditions

Packaging materials: metal.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	
67-63-0	Propan-2-ol	200	-		TWA (8 h)	
		400	-		STEL (15 min)	
1330-20-7	Xylene, mixed isomers	50	221		TWA (8 h)	
		100	442		STEL (15 min)	

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
67-63-0	2-Propanol	Acetone	40 mg/L	Urine	End of shift at end of workweek
67-64-1	Acetone	Acetone	50 mg/L	Urine	End of shift

8.2. Exposure controls

Protective and hygiene measures

Do not eat, drink, smoke or sneeze at the workplace. Wash hands before breaks and after work.

Eye/face protection

Wear tightly sealed safety glasses against possible splashes into the eyes. (DIN EN 166)

Hand protection

Tested protective gloves are to be worn: Butyl rubber. (EN ISO 374)

Valves & Injection Cleaner

Revision date: 17.05.2022

Product code: 1541

Page 6 of 13

Skin protection

Wear suitable solvent-proof protective clothing according to EN 465.

Respiratory protection

Provide for good ventilation, when develop aerosols/mist. In case of insufficient ventilation, wear suitable respiratory equipment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	blue
Odour:	aromatic

Changes in the physical state

Boiling point or initial boiling point and boiling range:	110 - 116 °C
---	--------------

Flash point:	-5 °C
--------------	-------

Lower explosion limits:	0,6 vol. %
-------------------------	------------

Upper explosion limits:	12 vol. %
-------------------------	-----------

Auto-ignition temperature:	> 200 °C
----------------------------	----------

Vapour pressure: (at 20 °C)	20 hPa
--------------------------------	--------

Density (at 20 °C):	0,807 g/cm ³
---------------------	-------------------------

Water solubility: (at 20 °C)	insoluble
---------------------------------	-----------

Solubility in other solvents

Organic solvents

9.2. Other information

No data

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No information available.

10.3. Possibility of hazardous reactions

No information available.

10.4. Conditions to avoid

Only use the material in places where open light, fire and other flammable sources can be kept away.

10.5. Incompatible materials

Oxidizing agents. acid, concentrated. Alkalis (alkalis), concentrated.

10.6. Hazardous decomposition products

Carbon monoxide (CO).
Carbon dioxide (CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Valves & Injection Cleaner

Revision date: 17.05.2022

Product code: 1541

Page 7 of 13

Acute toxicity

Harmful if inhaled.

ATEmix calculated

ATE (inhalation dust/mist) 4,839 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
1330-20-7	xylene				
	oral	LD50 4300 mg/kg	Rat		
	dermal	LD50 3200 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 21,7 mg/l	Rat		
	inhalation dust/mist	ATE 1,5 mg/l			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol				
	oral	LD50 5280 mg/kg	Rat		
	dermal	LD50 12800 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 47,5 mg/l	Rat		
67-64-1	acetone; propan-2-one; propanone				
	oral	LD50 5800 mg/kg	Rat	RTECS	
	dermal	LD50 20000 mg/kg	Rabbit	IUCLID	
	inhalation (4 h) vapour	LC50 76 mg/l	Rat		
64742-48-9	Hydrocarbons, C9-C11, n-Alkanes, Isoalkanes, Cyclenes, < 2% Aromates				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 >5000 mg/kg	Rabbit		
	inhalation (4 h) dust/mist	LC50 >5 mg/l	Rat		
64742-47-8	Hydrocarbons, C9-C11, Isoalkanes, Cycloalkanes, < 2% Aromates				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 >5000 mg/kg	Rabbit		
	inhalation (4 h) dust/mist	LC50 >5 mg/l	Rat		
	Poly[oxy(1,2-butanediyl)], .alpha.-(3-aminopropyl)-.gamma.-hydroxy-, C11-14-isoalkyl ethers, C13-rich (Polyetheramines)				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rabbit		

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Valves & Injection Cleaner

Revision date: 17.05.2022

Product code: 1541

Page 8 of 13

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (xylene)

May cause drowsiness or dizziness. (propan-2-ol; isopropyl alcohol; isopropanol; acetone; propan-2-one; propanone)

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (xylene)

Aspiration hazard

May be fatal if swallowed and enters airways.

Practical experience

Other observations

No information available.

SECTION 12: Ecological information

12.1. Toxicity

Valves & Injection Cleaner

Revision date: 17.05.2022

Product code: 1541

Page 9 of 13

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
1330-20-7	xylene					
	Acute fish toxicity	LC50 mg/l	26,7	96 h	Pimephales promelas	
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
	Acute fish toxicity	LC50 mg/l	9640	96 h	Pimephales promelas	
	Acute algae toxicity	ErC50 mg/l	1000	72 h	Algae	
	Acute crustacea toxicity	EC50 mg/l	13299	48 h	Daphnia magna	
67-64-1	acetone; propan-2-one; propanone					
	Acute fish toxicity	LC50 mg/l	5540	96 h	Onchorhynchus mykiss	
	Acute crustacea toxicity	EC50 mg/l	6100	48 h	Daphnia magna	
64742-48-9	Hydrocarbons, C9-C11, n-Alkanes, Isoalkanes, Cyclenes, < 2% Aromates					
	Acute fish toxicity	LC50 mg/l	>1000	96 h	Oncorhynchus mykiss	
	Acute algae toxicity	ErC50 mg/l	>1000	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50 mg/l	1000	48 h	Daphnia magna	
64742-47-8	Hydrocarbons, C9-C11, Isoalkanes, Cycloalkanes, < 2% Aromates					
	Acute fish toxicity	LC50 mg/l	>1000	96 h	Oncorhynchus mykiss	
	Acute algae toxicity	ErC50 mg/l	>1000	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50 mg/l	1000	48 h	Daphnia magna	
	Poly[oxy(1,2-butanediyl)], .alpha.-(3-aminopropyl)-.gamma.-hydroxy-, C11-14-isoalkyl ethers, C13-rich (Polyetheramines)					
	Acute fish toxicity	LC50 mg/l	1-10	96 h	Fish	
	Acute algae toxicity	ErC50 mg/l	10-100	72 h	Algae	

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

Swims on the water. Low potential of bio-accumulation.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-64-1	acetone; propan-2-one; propanone	-0,24

12.4. Mobility in soil

No information available.

12.6. Other adverse effects

No information available.

Valves & Injection Cleaner

Revision date: 17.05.2022

Product code: 1541

Page 10 of 13

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not dispose with household waste.

Do not allow to enter into surface water or drains.

Have to add a Special treatment in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

Arrange about the exact waste code with the local waste disposal expert.

Contaminated packaging

Contaminated packing must be completely emptied and can be re-used following appropriate cleaning.

Do not pierce, cut up or weld unclean container. (Explosion hazard.)

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:

UN 1993

14.2. UN proper shipping name:

FLAMMABLE LIQUID, N.O.S.

(xylene, propan-2-ol; isopropyl alcohol; isopropanol
acetone; propan-2-one; propanone, Hydrocarbons, C9-C11, n-Alkanes,
Isoalkanes, Cyclenes, < 2% Aromates)

14.3. Transport hazard class(es):

3

14.4. Packing group:

II

Hazard label:

3



Classification code:

F1

Special Provisions:

274 601 640D

Limited quantity:

1 L

Excepted quantity:

E2

Transport category:

2

Hazard No:

33

Tunnel restriction code:

D/E

Inland waterways transport (ADN)

14.1. UN number:

UN 1993

14.2. UN proper shipping name:

FLAMMABLE LIQUID, N.O.S.

(xylene, propan-2-ol; isopropyl alcohol; isopropanol
acetone; propan-2-one; propanone, Hydrocarbons, C9-C11, n-Alkanes,
Isoalkanes, Cyclenes, < 2% Aromates)

14.3. Transport hazard class(es):

3

14.4. Packing group:

II

Hazard label:

3



Classification code:

F1

Special Provisions:

274 601 640D

Limited quantity:

1 L

Excepted quantity:

E2


Valves & Injection Cleaner

Revision date: 17.05.2022


Product code: 1541

Page 11 of 13

Marine transport (IMDG)

14.1. UN number:	UN 1993
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (xylene, propan-2-ol; isopropyl alcohol; isopropanol acetone; propan-2-one; propanone, Hydrocarbons, C9-C11, n-Alkanes, Isoalkanes, Cyclenes, < 2% Aromates)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
	
Marine pollutant:	-
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:	UN 1993
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (xylene, propan-2-ol; isopropyl alcohol; isopropanol acetone; propan-2-one; propanone, Hydrocarbons, C9-C11, n-Alkanes, Isoalkanes, Cyclenes, < 2% Aromates)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
	
Special Provisions:	A3
Limited quantity Passenger:	1 L
Passenger LQ:	Y341
Excepted quantity:	E2
IATA-packing instructions - Passenger:	353
IATA-max. quantity - Passenger:	5 L
IATA-packing instructions - Cargo:	364
IATA-max. quantity - Cargo:	60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No information available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Valves & Injection Cleaner

Revision date: 17.05.2022

Product code: 1541

Page 12 of 13

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 40, Entry 75

2010/75/EU (VOC): 98,25 % (792,878 g/l)

2004/42/EC (VOC): 98,25 % (792,878 g/l)

Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

Additional information

Contains:

> 30 % hydrocarbons, aromatic.

15 - 30 % hydrocarbons, aliphatic.

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

xylene

propan-2-ol; isopropyl alcohol; isopropanol

acetone; propan-2-one; propanone

Hydrocarbons, C9-C11, n-Alkanes, Isoalkanes, Cyclenes, < 2% Aromates

Hydrocarbons, C9-C11, Isoalkanes, Cycloalkanes, < 2% Aromates

SECTION 16: Other information

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Acute Tox. 4; H332	Calculation method
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H335	Calculation method
STOT SE 3; H336	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

Valves & Injection Cleaner

Revision date: 17.05.2022

Product code: 1541

Page 13 of 13

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)