



according to Regulation (EC) No 1907/2006

Silicone Sealing Compound - grey -

Revision date: 17.05.2022

Product code: 1502

Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Silicone Sealing Compound - grey -

UFI:

1PV9-P07Q-FA0M-K2JR

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Sealing agent.

1.3. Details of the supplier of the safety data sheet

CTP GmbH	
Saalfelder Strasse 35h	
D-07338 Leutenberg	
+49 (0)36734 230-0	Telefax: +49 (0)36734 230-22
msds@bluechemgroup.com	
Jens Moeller, DiplChem.	Telephone: +49 (0)36734 230-19
www.bluechemgroup.com	
GBK GmbH: +49-(0)6132-84463 (24/7)	
	Saalfelder Strasse 35h D-07338 Leutenberg +49 (0)36734 230-0 msds@bluechemgroup.com Jens Moeller, DiplChem. www.bluechemgroup.com

number:

Further Information

Article Number: 39762

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Aerosol 3; H229 Skin Corr. 1B: H314 Eve Dam. 1: H318

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Triacetic oxy methylsilane

Propyltriacetic oxy silane

Signal word:

Pictograms:



Danger

Hazard statements

H229	Pressurised container: May burst if heated.
H314	Causes severe skin burns and eye damage.
Precautionary st	atements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.

1 102	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No
	smoking.
P251	Do not pierce or burn, even after use.





according to Regulation (EC) No 1907/2006

Silicone Sealing Compound - grey -

Revision date: 17.05.2022	Product code: 1502	Page 2 of 8
P280	Wear protective gloves.	
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.	
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P310	Immediately call a POISON CENTER/doctor.	
P405	Store locked up.	
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.	
P501	Dispose of this material and its container to hazardous or special waste collection point.	

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

silicones

Aerosols, non-flammable

Hazardous components

CAS No	No Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
4253-34-3	Triacetic oxy methylsilane			1 - < 5 %
	224-221-9		01-2119962266-32	
	Acute Tox. 4, Skin Corr. 1C, Eye D	am. 1; H302 H314 H318 EUH014		
17865-07-5	Propyltriacetic oxy silane			1 - < 5 %
	241-816-9		01-2119966899-07	
	Skin Corr. 1B; H314 EUH071			
811-97-2	1,1,1,2-tetra fluor ethane			1 - < 5 %
	212-377-0		01-2119459374-33	
	Liquefied gas; H280			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. L	imits, M-factors and ATE	
4253-34-3	224-221-9	Triacetic oxy methylsilane	1 - < 5 %
	oral: LD50 = 20)60 mg/kg	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove affected person from the danger area and lay down. Change contaminated clothing.

After inhalation

Provide fresh air. If victim is at risk of losing consciousness, position and transport on their side.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap.

In case of skin irritation, seek medical treatment.





according to Regulation (EC) No 1907/2006

Silicone Sealing Compound - grey -

Revision date: 17.05.2022

Product code: 1502

Page 3 of 8

After contact with eyes

If product gets into the eye, keep e4yelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an opthalmologist.

After ingestion

Do NOT induce vomiting. Consult physician.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

The following symptoms may occur:

unconsciousness. Intoxication. vomiting. drowsiness. Headache.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguishing powder. Carbon dioxide (CO2). Water fog. alcohol resistant foam.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Swims on the water. Vapours are heavier than air and will spread at floor level.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Cool endangered container in case of fire.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation. Wear suitable solvent-proof protective clothing according to EN 465. Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes. Do not breathe gas/fumes/vapour/spray.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

6.4. Reference to other sections

No data

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep only in the original container in a cool, well-ventilated place. Have to care for a good Ventilation at workplace.





according to Regulation (EC) No 1907/2006

Silicone Sealing Compound - grey -

Revision date: 17.05.2022

Product code: 1502

Page 4 of 8

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately. Wash hands before breaks and after work. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

The floor should be leak tight, jointless and not absorbent. Keep only in the original container in a cool, well-ventilated place. Do not store at temperatures over: 50 °C Heating causes rise in pressure with risk of bursting.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear tightly sealed safety glasses against possible splashes into the eyes.

Hand protection

Tested protective gloves are to be worn: FKM (Fluoroelastomer (Viton)).NBR (Nitrile rubber).

Respiratory protection

Have to care for a good Ventilation at workplace.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Paste
Colour:	grey
Odour:	characteristic
Changes in the physical state	
Density (at 20 °C):	
9.2. Other information	

1,00- 1,35 g/cm³

No data

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No decomposition when used as intended.

10.3. Possibility of hazardous reactions

No dangerous reactions are known.

10.4. Conditions to avoid

Do not store at temperatures over: 50 °C Keep away from heat.

10.5. Incompatible materials

No information available.





according to Regulation (EC) No 1907/2006

Silicone Sealing Compound - grey -

Revision date: 17.05.2022

Product code: 1502

Page 5 of 8

10.6. Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
4253-34-3	Triacetic oxy methylsilane				
		LD50 2060 mg/kg	Rat		

Irritation and corrosivity

Causes severe skin burns and eye damage. Causes serious eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Other information

No information available.

SECTION 12: Ecological information

12.1. Toxicity

No information available.

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains.



according to Regulation (EC) No 1907/2006



Silicone Sealing Compound - grey -

Revision date: 17.05.2022

Product code: 1502

Page 6 of 8

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not dispose with household waste.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances: hazardous waste

List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

Contaminated packaging

Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number:</u>	UN 1950
14.2. UN proper shipping name:	AEROSOLS
<u>14.3. Transport hazard class(es):</u>	2
14.4. Packing group:	-
Hazard label:	2.2
	2
Classification code:	5A
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0
Transport category:	3
Hazard No:	-
Tunnel restriction code:	E
Inland waterways transport (ADN)	
<u>14.1. UN number:</u>	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
14.4. Packing group:	-
Hazard label:	2.2
	$\langle \rangle$
	2
Classification code:	5A
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0
Marine transport (IMDG)	
<u>14.1. UN number:</u>	UN 1950





according to Regulation (EC) No 1907/2006

	Silicone Sealing Compound - grey -	
Revision date: 17.05.2022	Product code: 1502	Page 7 of 8
14.2. UN proper shipping name:	AEROSOLS	
14.3. Transport hazard class(es):	2.2	
14.4. Packing group:	-	
Hazard label:	2.2	
Marina nallutant:	22	
Marine pollutant: Special Provisions:	- 63, 190, 277, 327, 344, 381, 959	
Limited quantity:	1000 mL	
Excepted quantity:	E0	
EmS:	F-D, S-U	
Air transport (ICAO-TI/IATA-DGR)		
<u>14.1. UN number:</u>	UN 1950	
14.2. UN proper shipping name:	AEROSOLS, NON-FLAMMABLE	
14.3. Transport hazard class(es):	2.2	
14.4. Packing group:	-	
Hazard label:	2.2	
Special Provisions: Limited quantity Passenger:	A98 A145 A167 A802	
Passenger LQ:	30 kg G Y203	
Excepted quantity:	E0	
IATA-packing instructions - Passenger:	203	
IATA-max. quantity - Passenger:	75 kg	
IATA-packing instructions - Cargo:	203	
IATA-max. quantity - Cargo:	150 kg	
14.5. Environmental hazards		
ENVIRONMENTALLY HAZARDOUS:	No	
14.6. Special precautions for user		
No information available.		
14.7. Maritime transport in bulk according	to IMO instruments	
No information available.		
SECTION 15: Regulatory information		
15.1. Safety, health and environmental req	ulations/legislation specific for the substance or mixture	
EU regulatory information		
Restrictions on use (REACH, annex XVII) .	
Entry 75		
Information according to 2012/18/EU	Not subject to 2012/18/EU (SEVESO III)	
(SEVESO III):		
National regulatory information		
Water hazard class (D):	1 - slightly hazardous to water	
<u>15.2. Chemical safety assessment</u>	J,	
Teran onormour survey ussessment		

For the following substances of this mixture a chemical safety assessment has been carried out:





according to Regulation (EC) No 1907/2006

Silicone Sealing Compound - grey -

Revision date: 17.05.2022

Product code: 1502

Page 8 of 8

Triacetic oxy methylsilane Propyltriacetic oxy silane 1,1,1,2-tetra fluor ethane

SECTION 16: Other information

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 3; H229	On basis of test data
Skin Corr. 1B; H314	Bridging principle "Aerosols"
Eye Dam. 1; H318	Bridging principle "Aerosols"

Relevant H and EUH statements (number and full text)

H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
EUH014	Reacts violently with water.
EUH071	Corrosive to the respiratory tract.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)