

Brake Cleaner

Revision date: 24.05.2022

Product code: 1434

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Brake Cleaner

UFI: 7PSE-1WGF-GF3Q-5351

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Cleaning agent.

1.3. Details of the supplier of the safety data sheet

Company name:	CTP GmbH	
Street:	Saalfelder Strasse 35h	
Place:	D-07338 Leutenberg	
Telephone:	+49 (0)36734 230-0	Telefax: +49 (0)36734 230-22
e-mail:	msds@bluechemgroup.com	
Contact person:	Jens Moeller, Dipl.-Chem.	Telephone: +49 (0)36734 230-19
Internet:	www.bluechemgroup.com	

1.4. Emergency telephone number: GBK GmbH: +49-(0)6132-84463 (24/7)

Further Information

Article Number: 2201

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Aerosol 1; H222-H229
Asp. Tox. 1; H304
Skin Irrit. 2; H315
STOT SE 3; H336
Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Hydrocarbons, C6-C7, n-Alkanes, Isoalkanes, Cyclenes, < 5% n-hexane
Hydrocarbons C7, n-alkanes, iso-alkanes, cyclics

Signal word: Danger

Pictograms:



Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Brake Cleaner

Revision date: 24.05.2022

Product code: 1434

Page 2 of 10

Precautionary statements

- | | |
|-----------|--|
| P101 | If medical advice is needed, have product container or label at hand. |
| P102 | Keep out of reach of children. |
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P211 | Do not spray on an open flame or other ignition source. |
| P251 | Do not pierce or burn, even after use. |
| P261 | Avoid breathing aerosole. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P280 | Wear protective gloves. |
| P312 | Call a POISON CENTER/doctor if you feel unwell. |
| P410+P412 | Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. |
| P501 | Dispose of this material and its container to hazardous or special waste collection point. |

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



Hazard statements

H222-H229-H336

Precautionary statements

P101-P102-P210-P211-P251-P261-P271-P312-P410+P412-P501

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Surface tension compounds
Cleaning and care agent
Anti wear agents not classified
corrosion preventing agent
Fragrances

Aerosol propellant:
Propane/butane-mixture

Brake Cleaner

Revision date: 24.05.2022

Product code: 1434

Page 3 of 10

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
92128-66-0	Hydrocarbons, C6-C7, n-Alkanes, Isoalkanes, Cyclenes, < 5% n-hexane			25 - 50 %
	921-024-6		01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
64742-49-0	Hydrocarbons C7, n-alkanes, iso-alkanes, cyclics			25 - 50 %
	927-510-4		01-2119475515-33	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
124-38-9	carbon dioxide			2,5 - 10,0 %
	204-696-9			
	Compressed gas; H280			
75-28-5	isobutane			5 - < 10 %
	200-857-2		01-2119485395-27	
	Flam. Gas 1, Compressed gas; H220 H280			
74-98-6	propane			1 - < 5 %
	200-827-9		01-2119486944-21	
	Flam. Gas 1A, Compressed gas; H220 H280			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
92128-66-0	921-024-6	Hydrocarbons, C6-C7, n-Alkanes, Isoalkanes, Cyclenes, < 5% n-hexane	25 - 50 %
		inhalation: LC50 = >20 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg	
64742-49-0	927-510-4	Hydrocarbons C7, n-alkanes, iso-alkanes, cyclics	25 - 50 %
		inhalation: LC50 = 23,3 mg/l (vapours); dermal: LD50 = >2920 mg/kg; oral: LD50 = >5840 mg/kg	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove affected person from the danger area and lay down.
Change contaminated clothing.

After inhalation

Provide fresh air.
If victim is at risk of losing consciousness, position and transport on their side.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap.
In case of skin irritation, seek medical treatment.

After contact with eyes

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Consult physician.

Brake Cleaner

Revision date: 24.05.2022

Product code: 1434

Page 4 of 10

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguishing powder.
Carbon dioxide (CO₂).
Water fog.
alcohol resistant foam.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Swims on the water. Vapours are heavier than air and will spread at floor level.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Cool endangered container in case of fire.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation. Wear suitable solvent-proof protective clothing according to EN 465. Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes.
Do not breathe gas/fumes/vapour/spray.

6.2. Environmental precautions

Do not empty into drains or the aquatic environment.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

6.4. Reference to other sections

Explosive. Vapours may form explosive mixtures with air.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep only in the original container in a cool, well-ventilated place. Have to care for a good Ventilation at workplace.

Advice on protection against fire and explosion

Vapours may form explosive mixtures with air.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.
Remove contaminated, saturated clothing immediately. Wash hands before breaks and after work.
Do not breathe gas/fumes/vapour/spray. Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Brake Cleaner

Revision date: 24.05.2022

Product code: 1434

Page 5 of 10

Requirements for storage rooms and vessels

The floor should be leak tight, jointless and not absorbent. Keep only in the original container in a cool, well-ventilated place. Do not store at temperatures over: 50 °C
Heating causes rise in pressure with risk of bursting.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
124-38-9	Carbon dioxide	5000	9150		TWA (8 h)	WEL
		15000	27400		STEL (15 min)	WEL

8.2. Exposure controls

Appropriate engineering controls

Carbon dioxide (CO₂). MAK 5000 ppm

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear tightly sealed safety glasses against possible splashes into the eyes.

Hand protection

Tested protective gloves are to be worn: FKM (Fluoroelastomer (Viton)).NBR (Nitrile rubber).

Respiratory protection

Have to care for a good Ventilation at workplace.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Aerosol
Colour: colourless
Odour: characteristic/Lemon

Changes in the physical state

Flash point: not applicable
Density (at 20 °C): 0,706 g/cm³

9.2. Other information

Other safety characteristics

Solvent content: 96,6 %

Further Information

No data

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No decomposition when used as intended.

10.3. Possibility of hazardous reactions

Brake Cleaner

Revision date: 24.05.2022

Product code: 1434

Page 6 of 10

No dangerous reactions are known.

10.4. Conditions to avoid

Do not store at temperatures over: 50 °C

Keep away from heat.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
92128-66-0	Hydrocarbons, C6-C7, n-Alkanes, Isoalkanes, Cyclenes, < 5% n-hexane				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 >20 mg/l	Rat		
64742-49-0	Hydrocarbons C7, n-alkanes, iso-alkanes, cyclics				
	oral	LD50 >5840 mg/kg	Rat		
	dermal	LD50 >2920 mg/kg	Rat		
	inhalation (4 h) vapour	LC50 23,3 mg/l	Rat		

Irritation and corrosivity

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C6-C7, n-Alkanes, Isoalkanes, Cyclenes, < 5% n-hexane; Hydrocarbons C7, n-alkanes, iso-alkanes, cyclics)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

Other information

No information available.

SECTION 12: Ecological information

12.1. Toxicity

Brake Cleaner

Revision date: 24.05.2022

Product code: 1434

Page 7 of 10

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
92128-66-0	Hydrocarbons, C6-C7, n-Alkanes, Isoalkanes, Cyclenes, < 5% n-hexane					
	Acute fish toxicity	LC50 mg/l	11,4	96 h	Oncorhynchus mykiss	
	Acute algae toxicity	ErC50	30 mg/l	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50	3 mg/l	48 h	Daphnia magna	
64742-49-0	Hydrocarbons C7, n-alkanes, iso-alkanes, cyclics					
	Acute fish toxicity	LC50 mg/l	>13,4	96 h	fish	
	Acute algae toxicity	ErC50 mg/l	10-30	72 h	algae	
	Acute crustacea toxicity	EC50	3,0 mg/l	48 h	Dm	

12.2. Persistence and degradability

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
92128-66-0	Hydrocarbons, C6-C7, n-Alkanes, Isoalkanes, Cyclenes, < 5% n-hexane			
	Biodegradation	81%	28	
	Easily biodegradable (concerning to the criteria of the OECD)			

12.3. Bioaccumulative potential

Swims on the water.

Low potential of bio-accumulation.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
75-28-5	isobutane	2,8
74-98-6	propane	2,36

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not empty into drains or the aquatic environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

According to EAKV, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Arrange about the exact waste code with the local waste disposal expert.

Brake Cleaner

Revision date: 24.05.2022

Product code: 1434

Page 8 of 10

Do not dispose with household waste.

Contaminated packaging

Dispose of waste according to applicable legislation. Contaminated packing must be completely emptied and can be re-used following appropriate cleaning.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
 Propane/butane-mixture
14.3. Transport hazard class(es): 2
14.4. Packing group: -
 Hazard label: 2.1



Classification code: 5F
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L
 Excepted quantity: E0
 Transport category: 2
 Hazard No: -
 Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
 Propane/butane-mixture
14.3. Transport hazard class(es): 2
14.4. Packing group: -
 Hazard label: 2.1



Classification code: 5F
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L
 Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
 Propane/butane-mixture
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
 Hazard label: 2.1



Marine pollutant: P

Brake Cleaner

Revision date: 24.05.2022

Product code: 1434

Page 9 of 10

Special Provisions: 63, 190, 277, 327, 344, 381, 959
Limited quantity: 1000 mL
Excepted quantity: E0
EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS, FLAMMABLE
Propane/butane-mixture
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
Hazard label: 2.1



Special Provisions: A145 A167 A802
Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0
IATA-packing instructions - Passenger: 203
IATA-max. quantity - Passenger: 75 kg
IATA-packing instructions - Cargo: 203
IATA-max. quantity - Cargo: 150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



Danger releasing substance: Hydrocarbons, C6-C7, n-Alkanes, Isoalkanes, Cyclenes, < 5% n-hexane
Hydrocarbons C7, n-alkanes, iso-alkanes, cyclics

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

No information available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 40, Entry 75

2010/75/EU (VOC): 52 % (367,12 g/l)
2004/42/EC (VOC): 52 % (367,12 g/l)
Information according to 2012/18/EU (SEVESO III): P3a FLAMMABLE AEROSOLS
Additional information: E2

Additional information

Contains:
> 30 % aliphatic hydrocarbons
< 5 % Fragrances (D-Limonene, Citral)

National regulatory information

Brake Cleaner

Revision date: 24.05.2022

Product code: 1434

Page 10 of 10

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

Hydrocarbons, C6-C7, n-Alkanes, Isoalkanes, Cyclohexanes, < 5% n-hexane

Hydrocarbons C7, n-alkanes, iso-alkanes, cyclics

isobutane

propane

SECTION 16: Other information

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)