

**Octane Premium**

Revision date: 25.05.2022

Product code: 1689

Page 1 of 11

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Octane Premium

UFI: H9HA-H3CM-WDSV-TN24

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Increase the ROZ-octane number.

**1.3. Details of the supplier of the safety data sheet**

Company name:	CTP GmbH	
Street:	Saalfelder Strasse 35h	
Place:	D-07338 Leutenberg	
Telephone:	+49 (0)36734 230-0	Telefax: +49 (0)36734 230-22
e-mail:	msds@bluechemgroup.com	
Contact person:	Jens Moeller, Dipl.-Chem.	Telephone: +49 (0)36734 230-19
Internet:	www.bluechemgroup.com	

**1.4. Emergency telephone number:** GBK GmbH: +49-(0)6132-84463 (24/7)**Further Information**

Article Number: 33280, 33289, 33285, 33281, 33282, 33283

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Flam. Liq. 3; H226  
Acute Tox. 4; H302  
Acute Tox. 4; H332  
Asp. Tox. 1; H304  
Skin Irrit. 2; H315  
Eye Irrit. 2; H319  
Carc. 2; H351  
STOT SE 3; H335  
STOT RE 2; H373  
Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

**2.2. Label elements****Regulation (EC) No 1272/2008****Hazard components for labelling**

xylene  
tricarbonyl(methylcyclopentadienyl)manganese (MMT)  
Hydrocarbons, C10, aromatics, >1% naphthalene

**Signal word:** Danger**Pictograms:****Hazard statements**

H226 Flammable liquid and vapour.

## Octane Premium

Revision date: 25.05.2022

Product code: 1689

Page 2 of 11

H302+H332	Harmful if swallowed or if inhaled.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.


### Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe Vapour/Smoke/aerosole.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves and eye/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P312	Call a POISON CENTER/doctor if you feel unwell.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P391	Collect spillage.
P405	Store locked up.
P501	Dispose of this material and its container to hazardous or special waste collection point.

### Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



### Hazard statements

H302+H332-H304-H335-H351-H373

### Precautionary statements

P101-P102-P260-P270-P271-P280-P331-P312-P405-P501

### 2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Chemical characterization

Ignition improver

## Octane Premium

Revision date: 25.05.2022

Product code: 1689

Page 3 of 11

### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
1330-20-7	xylene			85 - < 90 %
	215-535-7		01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H226 H332 H312 H315 H319 H335 H373 H304 H412			
12108-13-3	tricarbonyl(methylcyclopentadienyl)manganese (MMT)			5 - < 10 %
	235-166-5		01-2119495971-23	
	Acute Tox. 1, Acute Tox. 2, Acute Tox. 3, Skin Irrit. 2, STOT RE 1, Aquatic Acute 1, Aquatic Chronic 1; H330 H310 H301 H315 H372 H400 H410			
64742-94-5	Hydrocarbons, C10, aromatics, >1% naphthalene			5 - < 10 %
	919-284-0		01-2119463588-24	
	Carc. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H351 H336 H304 H411			

Full text of H and EUH statements: see section 16.

### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
1330-20-7	215-535-7	xylene	85 - < 90 %
		inhalation: LC50 = 21,7 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 3200 mg/kg; oral: LD50 = 4300 mg/kg	
12108-13-3	235-166-5	tricarbonyl(methylcyclopentadienyl)manganese (MMT)	5 - < 10 %
		inhalation: LC50 = 0,22 mg/l (vapours); inhalation: LC50 = 0,076 mg/l (dusts or mists); dermal: LD50 = 196,7 mg/kg; oral: LD50 = 58 mg/kg	

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

Move victim to fresh air. Put victim at rest and keep warm.

#### After inhalation

Move victim to fresh air. Put victim at rest and keep warm.

In case of difficulties of breathing consult physician.

If victim is at risk of losing consciousness, position and transport on their side.

#### After contact with skin

Take off immediately all contaminated clothing, including underwear and shoes .

After contact with skin, wash immediately with plenty of water and soap.

Rub greasy ointment into the skin.

#### After contact with eyes

Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart.

Consult physician.

#### After ingestion

Let water be drunken in little sips (dilution effect). Consult physician.

### 4.2. Most important symptoms and effects, both acute and delayed

Frequently or prolonged contact with skin may cause dermal irritation.

Irritation of eyes: Irritant effect possible.

After ingestion: Harmful: may cause lung damage if swallowed.

Harmful by inhalation.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

**bluechem**   
**GROUP**

### Octane Premium

Revision date: 25.05.2022

Product code: 1689

Page 4 of 11

#### **4.3. Indication of any immediate medical attention and special treatment needed**

Warning about danger of aspiration.

### **SECTION 5: Firefighting measures**

#### **5.1. Extinguishing media**

##### **Suitable extinguishing media**

Extinguishing powder.

Sand.

alcohol resistant foam.

Carbon dioxide (CO<sub>2</sub>).

##### **Unsuitable extinguishing media**

High power water jet.

#### **5.2. Special hazards arising from the substance or mixture**

Formation of decomposition products possible.

In case of fire and/or explosion do not breathe fumes.

#### **5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

##### **Additional information**

Cool endangered container in case of fire.

Contaminated fire-fighting water must be collected separately.

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

##### **General advice**

In case of fire: Wear self-contained breathing apparatus.

Keep away from sources of ignition - No smoking.

#### **6.2. Environmental precautions**

Beat down gas/vapours/mist with water spray.

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

#### **6.3. Methods and material for containment and cleaning up**

##### **Other information**

Prevent spreading of spillages (e.g. by oil barrier).

Wipe up with absorbent material (eg. cloth, fleece).

#### **6.4. Reference to other sections**

No data

### **SECTION 7: Handling and storage**

#### **7.1. Precautions for safe handling**

##### **Advice on safe handling**

Closed devices. Vapours / aerosols must be extracted by suction immediately at point of origin.

Avoid contact with skin and eyes.

##### **Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharges.

##### **Advice on general occupational hygiene**

When using do not eat, drink or smoke.

Wash hands before breaks and after work.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Octane Premium

Revision date: 25.05.2022

Product code: 1689

Page 5 of 11

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

##### Further information on storage conditions

Packaging materials: metal.

#### 7.3. Specific end use(s)

No information available.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Occupational exposure limits

CAS No	Substance	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
12108-13-3	Methylcyclopentadienyl manganese, tricarbonyl (as Mn)	-	0.2		TWA (8 h)	
1330-20-7	Xylene, mixed isomers	50	221		TWA (8 h)	
		100	442		STEL (15 min)	

#### 8.2. Exposure controls

##### Individual protection measures, such as personal protective equipment

###### Eye/face protection

Wear tightly sealed safety glasses against possible splashes into the eyes. (DIN EN 166)

###### Hand protection

Tested protective gloves are to be worn: Butyl rubber. (EN ISO 374)

###### Skin protection

Wear suitable solvent-proof protective clothing according to EN 465.

###### Respiratory protection

In case of accumulation of fumes/aerosols, provide adequate ventilation.

In case of insufficient ventilation, wear suitable respiratory equipment.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	reddish brown
Odour:	characteristic

##### Changes in the physical state

Flash point: 24 °C

Water solubility: insoluble  
(at 20 °C)

##### Solubility in other solvents

Organic solvents

Density (at 15 °C): 0,87 - 0,89 g/cm<sup>3</sup>

#### 9.2. Other information

No data

## Octane Premium

Revision date: 25.05.2022

Product code: 1689

Page 6 of 11

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No information available.

#### 10.2. Chemical stability

No decomposition when used as intended.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions are known.

#### 10.4. Conditions to avoid

Only use the material in places where open light, fire and other flammable sources can be kept away.

#### 10.5. Incompatible materials

Oxidizing agents.

acid, concentrated.

Alkalis (alkalis), concentrated.

#### 10.6. Hazardous decomposition products

Carbon monoxide (CO).

Carbon dioxide (CO<sub>2</sub>).

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Acute toxicity

Harmful if swallowed.

Harmful if inhaled.

##### ATEmix tested

	Dose	Species	Source
LD50, oral	1000 mg/kg	Rat	
LD50, dermal	2958 mg/kg	Rabbit	
LC50, inhalation (vapour) (4 h)	14,79 mg/l	Rat	
LC50, inhalation (dust/mist) (4 h)	1,17 mg/l	Rat	
LC50, inhalation (gas) (4 h)	7142 ppm	Rat	

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
1330-20-7	xylene				
	oral	LD50 4300 mg/kg	Rat		
	dermal	LD50 3200 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 21,7 mg/l	Rat		
	inhalation dust/mist	ATE 1,5 mg/l			
12108-13-3	tricarbonyl(methylcyclopentadienyl)manganese (MMT)				
	oral	LD50 58 mg/kg	Rat		
	dermal	LD50 196,7 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 0,22 mg/l	Rat		
	inhalation (4 h) dust/mist	LC50 0,076 mg/l	Rat		

## Octane Premium

Revision date: 25.05.2022

Product code: 1689

Page 7 of 11

### Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

### Sensitising effects

Based on available data, the classification criteria are not met.

### Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing cancer. (Hydrocarbons, C10, aromatics, >1% naphthalene)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

### STOT-single exposure

May cause respiratory irritation. (xylene)

### STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (xylene; tricarbonyl(methylcyclopentadienyl)manganese (MMT))

### Aspiration hazard

May be fatal if swallowed and enters airways.

### Information on likely routes of exposure

## 11.2. Information on other hazards

### Other information

No information available.

## SECTION 12: Ecological information

### 12.1. Toxicity

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
1330-20-7	xylene					
	Acute fish toxicity	LC50 26,7 mg/l	96 h	Pimephales promelas		
12108-13-3	tricarbonyl(methylcyclopentadienyl)manganese (MMT)					
	Acute fish toxicity	LC50 0,21 mg/l	96 h	Cyprinus carpio (Carp)		
	Acute algae toxicity	ErC50 1,7 mg/l	72 h	Algae		
	Acute crustacea toxicity	EC50 0,83 mg/l	48 h	Daphnia magna		
64742-94-5	Hydrocarbons, C10, aromatics, >1% naphthalene					
	Acute fish toxicity	LC50 2-5 mg/l	96 h	Fish		
	Acute algae toxicity	ErC50 1-3 mg/l	72 h	Algae		
	Acute crustacea toxicity	EC50 3-10 mg/l	48 h	Daphnia magna		

### 12.2. Persistence and degradability

No information available.

### 12.3. Bioaccumulative potential

Low potential of bio-accumulation.

### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
12108-13-3	tricarbonyl(methylcyclopentadienyl)manganese (MMT)	3,4



## Safety Data Sheet

bluechem   
GROUP

according to Regulation (EC) No 1907/2006

### Octane Premium

Revision date: 25.05.2022

Product code: 1689

Page 8 of 11

#### **12.4. Mobility in soil**

No information available.

#### **12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### **12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### **12.7. Other adverse effects**

No information available.

### **SECTION 13: Disposal considerations**

#### **13.1. Waste treatment methods**

##### **Disposal recommendations**

Do not dispose with household waste.

Do not allow to enter into surface water or drains.

Have to add a Special treatment in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

Arrange about the exact waste code with the local waste disposal expert.

##### **Contaminated packaging**

Contaminated packing must be completely emptied and can be re-used following appropriate cleaning.

Do not pierce, cut up or weld unclean container. (Explosion hazard.)

### **SECTION 14: Transport information**

#### **Land transport (ADR/RID)**

<b><u>14.1. UN number:</u></b>	UN 1307
<b><u>14.2. UN proper shipping name:</u></b>	XYLENES
<b><u>14.3. Transport hazard class(es):</u></b>	3
<b><u>14.4. Packing group:</u></b>	III
Hazard label:	3



Classification code:	F1
Special Provisions:	-
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	30
Tunnel restriction code:	D/E

#### **Inland waterways transport (ADN)**

<b><u>14.1. UN number:</u></b>	UN 1307
<b><u>14.2. UN proper shipping name:</u></b>	XYLENES
<b><u>14.3. Transport hazard class(es):</u></b>	3
<b><u>14.4. Packing group:</u></b>	III
Hazard label:	3



## Octane Premium

Revision date: 25.05.2022

Product code: 1689

Page 9 of 11



Classification code: F1  
Special Provisions: -  
Limited quantity: 5 L  
Excepted quantity: E1

### Marine transport (IMDG)

**14.1. UN number:** UN 1307  
**14.2. UN proper shipping name:** XYLENES  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Marine pollutant: P  
Special Provisions: 223  
Limited quantity: 5 L  
Excepted quantity: E1  
EmS: F-E, S-D

### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 1307  
**14.2. UN proper shipping name:** XYLENES  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Special Provisions: A3  
Limited quantity Passenger: 10 L  
Passenger LQ: Y344  
Excepted quantity: E1  
IATA-packing instructions - Passenger: 355  
IATA-max. quantity - Passenger: 60 L  
IATA-packing instructions - Cargo: 366  
IATA-max. quantity - Cargo: 220 L

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



Danger releasing substance: tricarbonyl(methylcyclopentadienyl)manganese (MMT)  
Hydrocarbons, C10, aromatics, >1% naphthalene

### 14.6. Special precautions for user

No information available.

### 14.7. Maritime transport in bulk according to IMO instruments

No information available.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Octane Premium

Revision date: 25.05.2022

Product code: 1689

Page 10 of 11

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

2010/75/EU (VOC): 86 % (748,2 g/l)

2004/42/EC (VOC): 86 % (748,2 g/l)

Information according to 2012/18/EU (SEVESO III): E2 Hazardous to the Aquatic Environment

Additional information: P5c

#### Additional information

Contains:

> 30 % hydrocarbons, aromatic.

#### National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

### 15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

xylene

tricarbonyl(methylcyclopentadienyl)manganese (MMT)

Hydrocarbons, C10, aromatics, >1% naphthalene

## SECTION 16: Other information

### Changes

This data sheet contains changes from the previous version in section(s): 2,11,12,14,15.

### Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Acute Tox. 4; H302	On basis of test data
Acute Tox. 4; H332	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Carc. 2; H351	Calculation method
STOT SE 3; H335	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 2; H411	Calculation method

### Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H302+H332	Harmful if swallowed or if inhaled.
H304	May be fatal if swallowed and enters airways.
H310	Fatal in contact with skin.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.



## Safety Data Sheet

**bluechem**   
**GROUP**

according to Regulation (EC) No 1907/2006

### Octane Premium

Revision date: 25.05.2022

Product code: 1689

Page 11 of 11

H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

#### Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*